
# HP Everyday Adhesive Matte Polypropylene, 2 Pack





## The HP Designjet printing system—the complete solution

HP Designjet printers, Original HP inks and printheads, and Original HP printing materials are designed to work together as a system to provide reliable, consistent results with every print.



- HP Everyday Adhesive Matte Polypropylene can be easily removed. Residual adhesive can be easily wiped clean. Some warranty limitations apply, see the Limited Warranty statement at <a href="hp.com/go/">hp.com/go/</a> HPMediaWarranties.
- With Original HP 771 Vivid Photo Inks, Original HP 91 Photo Inks, or Original HP 70 Photo Inks on the HP Designjet Z3200 Photo Printer series. Display permanence rating for interior displays/away from direct sunlight, under glass by HP Image Permanence Lab and/or by Wilhelm Imaging Research, Inc. on a range of HP media. For more information, see hp.com/go/supplies/printpermanence.

### High-quality prints for your day-to-day production

#### Produce eye-catching displays

See outstanding image quality. Work with the wide color gamut and smooth transitions delivered by this matte polypropylene material and produce quality prints from line drawings to photo-quality POP displays.

#### **Gain efficiency**

Help keep your production process moving smoothly. This easy-to-use film features a permanent self adhesive for secure, reliable mounting. Instant-dry prints can be easily removed.<sup>1</sup>

#### Make the versatility of this material work for you

ICC profiles help you get the right color, right away. Take advantage of compatibility with HP dye and pigment inks. Offer over 50 years unlaminated indoor display permanence,<sup>2</sup> on this versatile, easy-to-use printing material.

Target customers	Applications	Benefits		
Print service providers	POP and retail displays	Outstanding image quality for day-to-day production		
Retail store in-house printing	Trade show and event displays	Instant dry time		
Event designers	Temporary exhibitions	A permanent self-adhesive for secure, reliable mounting		
Advertising agencies	Architecture competitions	Compatible with both HP dye- and pigment-based inks		
Geographic Information Systems (GIS) Government (printing self-adhesive maps)	i	50+ years unlaminated indoor display permanence on HP Designjet Z-series printers <sup>2</sup>		
		Easy to use and remove, with a limited HP warranty <sup>1</sup>		
		Broad HP Designjet printer compatibility <sup>3</sup>		





## **Technical specifications**





#### HP Everyday Adhesive Matte Polypropylene, 2 Pack

For the latest ICC/media profiles and a variety of resources to help you get the most out of your printer and HP large format printing materials, please visit hp.com/go/LFPrintingMaterials.

Weight (without liner)	120 g/m² per ISO	536 Test M	1ethod				
Weight (with liner)	168 g/m² per ISO 536 Test Method						
Thickness (without liner)	180 microns/7.1 mil per ISO 534 Test Method						
Thickness (with liner)	215 microns/8.5 mil per ISO 534 Test Method						
Opacity (with liner)	Greater than 96% per TAPPI T-425 and ISO 2471 Test Methods						
Brightness (with liner)	101% per ISO 2470 Test Method						
Whiteness (without liner)	Greater than 120 per ISO 11476 Test Method						
Whiteness (with liner)	150 per ISO 11475 Test Method						
Finish	Matte						
Operating temperature	15 to 35° C / 59 to 95° F						
Operating humidity	20 to 80% RH						
Display permanence	50+ years unlaminated with Original HP 771 Vivid Photo Inks, Original HP 91 Photo Inks, or Original HP 70 Photo						
(Indoor home or office)	Inks on the HP Designjet Z3200 Photo Printer series <sup>4</sup>						
Water resistance	Moderately water resistant with Original HP 771 Vivid Photo Inks, Original HP 91 Photo Inks, or Original HP 70 Photo Inks on the HP Designjet Z3200 Photo Printer series; lamination recommended with Original HP dye inks <sup>5</sup>						
Dry time	Less than 2 minutes (at 23° C, 50% RH)						
Lamination	Yes						
Shelf life	2 years, unopened in original packaging						
Storage temperature	15 to 35° C / 59 to 95° F						
Storage humidity	15 to 30% RH						
Country of origin	Product of China						
Ordering information	Product numbers	Quantity	Roll sizes	UPC codes	Region		
	COF18A <sup>6</sup>	2 Pack	610 mm x 22,9 m (24 in x75 ft)	887111205940	Worldwide		
	COF19A <sup>6</sup>	2 Pack	914 mm x 22,9 m (36 in x75 ft)	887111205957	Worldwide		
	COF20A <sup>6</sup>	2 Pack	1067 mm x 22,9 m (42 in x 75 ft)	887111205964	Worldwide		
	COF22A <sup>6</sup>	2 Pack	1524 mm x 22,9 m (60 in x 75 ft)	887111205988	Worldwide		
Warranty	7 , 1						

<sup>&</sup>lt;sup>4</sup> Display permanence rating for interior displays/away from direct sunlight, under glass by HP Image Permanence Lab and/or by Wilhelm Imaging Research, Inc. on a range of HP media. For more information, see hp.com/go/supplies/printpermanence.

# For detailed information on the HP large format printing materials portfolio and to order, see hp.com/go/LFPrintingMaterials

© 2013 Hewlett-Packard Development Company, L.P. The information contained herein is subject to change without notice. The only warranties for HP products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. HP shall not be liable for technical or editorial errors or omissions contained herein.



Water resistance testing by HP Image Permanence Lab on a range of HP media and follows ISO 18935 method. For more information, see <a href="hp.com/go/supplies/printpermanence">hp.com/go/supplies/printpermanence</a>.

<sup>&</sup>lt;sup>6</sup> Requires 2-inch spindle for compatibility with the HP Designjet L25500 and L26500 Printer series.