

Wide Format Laminiator

RSC-1401/1651HCLTW



- New width, laminate up to 1400mm / 55" (1650mm/65")
- High quality silicone rubber rollers
- **Mounting up to 15mm / 0.6"**
- Chain-driven synchronized take-up device
- 9 speed settings up to 5m/min / 16.4 ft/min
- Foot pedal control
- **Heat-assist top roller (up to 50°C)**
- Auto-Grip Hubs for easy replacement of film rolls
- **Laser system for safety**
- **Backing paper bar**

Description	RSC-1401HCLTW	RSC-1651HCLTW
Power supply	AC100-120, or 220~240V 50/60Hz	AC100-120, or 220~240V 50/60Hz
Power consumption	1500 W	1600 W
Max laminating width	1400mm / 55"	1650mm / 65"
Film thickness	50 ~ 500mic / 2~20mil	50 ~ 500mic / 2~20mil
Max laminating speed	5m/min / 16.4 ft/min	5m/min / 16.4 ft/min
Heating method	Hot roller	Hot roller
Drive motor	DC geared	DC geared
Max. temperature control	50°C / 122°F	50°C / 122°F
Speed control	9 settings	9 settings
Transport type	2 Roller	2 Roller
Film core size	Auto grip (2", 3")	Auto grip (2", 3")
Hot lamination	Yes (Top Roller)	Yes (Top Roller)
Cold lamination	Yes	Yes
Mounting thickness	15mm / 0.6"	15mm / 0.6"
Reverse	Yes	Yes
Safety System	Laser System for Safety	Laser System for Safety
Foot pedal	Yes	Yes
Back Paper	Yes	Yes
Unit dimensions (w x d x h)	1710 x 550 x 1110 (mm)	1950 x 550 x 1110 (mm)